



# Built To Your Specs

## XRI 500/600

The XRI is an industrial machine that can be built to custom specifications for commercial orders of as low as 12 machines. RUESCH will also accessorize the vehicle with equipment and tools which are needed in your particular line of work at a significant cost savings. At RUESCH we understand that different applications have different requirements. We will source your specific needs and give our commercial accounts the exact machine they want right out of the box.



Available in XR or XRL



### EQUIPMENT OPTIONS

- Custom Cargo Box
- Water Tanks
- Tool Racks
- Welder
- Generator
- Air Compressor
- Roll Cage Enclosure
- Fire Extinguisher
- First Aid Kit

# INDUSTRIAL STRENGTH

[www.Ruesch.US](http://www.Ruesch.US)

# RÜESCH

## SPECIFICATIONS



### XRI

|                  |   |                          |   |                                  |
|------------------|---|--------------------------|---|----------------------------------|
| Engine           | • | CF Moto Single Cyl       | • | <b>VEHICLE OPTIONS</b>           |
| Horsepower       | • | 35 HP                    | • |                                  |
| Maximum Speed    | • | 45                       | • | <b>Roll Over Warning System</b>  |
| Drive            | • | 2 & 4 Wheel              | • | <b>Over Load Limit Indicator</b> |
| Exhaust          | • | Dual Big Bore            | • | <b>Puncture Resistant Tires</b>  |
| Cooling          | • | Liquid                   | • | <b>4,000 lb Winch</b>            |
| Transmission     | • | V-Belt H-L-N-R           | • | <b>Turn Signals</b>              |
| Ignition         | • | CDI                      | • | <b>Windshield and Wiper</b>      |
| Starting         | • | Electric                 | • | <b>Full Roll Cage</b>            |
| Drive Train      | • | Shaft                    | • | <b>5 Point Safety Harness</b>    |
| Differential     | • | 3 Way Locking Diff       | • | <b>Auxiliary Power Package</b>   |
| Engine Braking   | • | All Wheel                | • | <b>Heavy Duty Shocks</b>         |
| Brakes           | • | Hydraulic Disk           | • | <b>LED Light Bars</b>            |
| Fuel             | • | 7.8 Gal                  | • |                                  |
| Lighting         | • | Fully Encased w/ blinker | • |                                  |
| Spot Lights      | • | 3 - LED system           | • |                                  |
| Gauges           | • | Tach, Oil, Speed, Temp   | • |                                  |
| Roll Cage        | • | Adjustable Clamp         | • |                                  |
| Wheels           | • | Custom Alloy             | • |                                  |
| Tires            | • | Mud Terrain              | • |                                  |
| Front Tires      | • | 25 - 8 - 12              | • |                                  |
| Rear Tires       | • | 25 - 10 - 12             | • |                                  |
| Long Travel      | • | Plus 9 over              | • |                                  |
| Suspension       | • | Independant Dual Arm     | • |                                  |
| Bushings         | • | Rubber                   | • |                                  |
| Camber           | • | Fixed                    | • |                                  |
| Shocks           | • | TSS Shocks               | • |                                  |
| Dampening        | • | Yes                      | • |                                  |
| Ground Clearance | • | 9 Inches                 | • |                                  |
| Front Travel     | • | 8 Inches                 | • |                                  |
| Rear Travel      | • | 8 Inches                 | • |                                  |
| Seats            | • | High Back Race           | • |                                  |
| Seat Belts       | • | 4 or 5 point Harness     | • |                                  |
| Steering Wheel   | • | Sure Grip                | • |                                  |
| Dry Weight       | • | 1124 lbs                 | • |                                  |
| Max Load         | • | 650 lbs                  | • |                                  |
| Length           | • | 116"                     | • |                                  |
| Width            | • | XR 54" XRM 64"           | • |                                  |